Slim and space-saving filling cabinets certified fire protection for up to one hour



Lateral Fire File

FIRE RESISTANT DOCUMENT PROTECTION


Key features


- Certified by UL (Underwriters Laboratories) to Class 350 Endurance 1 hour according to Standard 72
- Perfectly designed for today's modern offices,
 Chubbsafes Lateral Fire Files sit closer to the wall for marginally more filing than traditional large filing cabinets, offering exceptional functionality and optimized storage
- Maximised storage capacity that allows users to gain full advantage for their storage requirements.
 Chubbsafes Lateral Fire File is available with 3 or 4 drawers
- Easy operable day catch to secure the drawers when closed. Units do not have to be locked to provide fire protection but just be pushed closed


- High-quality steel sliders to ensure comfortable operation and full drawer access
- Low-weight cabinets for reduced transportation and installation costs, and lighter floor loads.
- All models fitted with high-security locks as standard
- Light grey, powder-coated finish and modern design which blends nicely into any office environment
- Chubbsafes Lateral Fire File is manufactured in accordance with ISO 9001 for quality management systems and ISO 14001 for environmental management systems



	External (mm)			Drawer dimensions (mm)				
Model	Height	Width	Depth	Height	Width	Depth	Weight (kg)	Capacity (litres)
3 drawers	1147	964	586	290	800	387	328	270
4 drawers	1510	964	586	290	800	387	411	359







4 drawers

Lock Options





Combination lock

Chubbsafes Lateral Fire File models are fitted with high-security locks as standard. They can be equipped with a central key lock for single locking or together with a mechanical combination lock for dual central locking. In addition each individual drawer can be fitted with a key lock.

Color: Light Grey RAL 7035

The Chubbsafes Lateral Fire File cabinets are tested and certified according to the most common and well-established UL (Underwriter's Laboratories) Standard 72 to Class 350 1 hour Fire Endurance. The product is subjected to extensive fire testing which simulates the impact of a severe fire. This two-step process includes the following:

Step 1

The filing cabinet is placed in a furnace and heated to a temperature of 1000°C. The furnace is switched off after one hour. The unit remains in the furnace until the temperature returns to ambient levels. The content is then examined for signs of damage. Both during furnace heating and the subsequent cooling period, the recorded internal temperature must not have exceeded 177°C (or 350°F).

Step 2

Fire Explosion or Shock Test. To simulate sudden heating, possibly as a result of rapid fire spread, the cabinet is inserted into a preheated furnace. The stresses and strains such rapid heating creates can easily cause a poorly constructed unit to fail. At all times internal temperatures are not allowed to exceed those set for the Step 1 fire endurance test.

Authorised dealer

www.coffreclesfavre.ch



www.chubbsafes.com